

# SV-QSFP-100G-LR4L

100GBase aggregating 4 x duplex LWDM (1295.6 nm, 1300.1 nm, 1304.6 nm, and 1309.1nm) wavelengths SM (LC) with DDM, distance up to 2km,



## Features

- Hot pluggable QSFP28 MSA form factor
- Compliant to IEEE 802.3ba 100GBASE-LR4
- Supports 103.1Gb/s aggregate bit rate
- Up to 2km reach for G.652 SMF
- Single +3.3V power supply
- Operating case temperature: 0~70°C
- Transmitter: cooled 4x25Gb/s LAN WDM DFB TOSA (1295.56, 1300.05, 1304.58, 1309.14nm)
- Receiver: 4x25Gb/s PIN ROSA
- 4x25G electrical interface (OIF CEI-28G-VSR)
- Maximum power consumption 4.0W
- Duplex LC receptacle
- RoHS-6 compliant

## Applications

- 100GBASE-LR4 Ethernet Links
- Infiniband QDR and DDR interconnects
- Datacenter and Enterprise networking

Part number	Description
SV-QSFP-100G-LR4L	Starview QSFP28 100Gbps module 100GBase aggregating 4 x duplex LWDM (1295.6 nm, 1300.1 nm, 1304.6 nm, and 1309.1nm) wavelengths SM (LC) with Digital Diagnostic Monitoring (DDM), distance up to 2km, supporting 100GE, Infiniband QDR and DDR

## Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit
Storage Temperature	T <sub>s</sub>	-40	85		degC
Operating Case Temperature	T <sub>OP</sub>	0	70		degC
Power Supply Voltage	V <sub>CC</sub>	-0.5	3.6		V
Relative Humidity (non-condensation)	RH	0	85		%
Damage Threshold, each Lane	TH <sub>d</sub>	5.5			dBm

## Recommended Operating Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Operating Case Temperature	T <sub>OP</sub>	0		70	degC	
Power Supply Voltage	V <sub>CC</sub>	3.135	3.3	3.465	V	
Data Rate, each Lane			25.78125		Gb/s	
Data Rate Accuracy		-100		100	ppm	
Control Input Voltage High		2		V <sub>CC</sub>	V	
Control Input Voltage Low		0		0.8	V	
Link Distance with G.652	D	0.002		2	km	

## Optical Characteristics

QSFP28 100GBASE-LR4							
Parameter	Symbol	Min.	Typ.	Max.	Unit	Note	
Lane Wavelength	L0	1294.53	1295.56	1296.59	nm		
	L1	1299.02	1300.05	1301.09	nm		
	L2	1303.54	1304.58	1305.63	nm		
	L3	1308.09	1309.14	1310.19	nm		
Transmitter							
SMSR	SMSR	30			dB		
Total Average Launch Power	P <sub>T</sub>			10.5	dBm		
Average Launch Power, each Lane	P <sub>AVG</sub>	-4.3		4.5	dBm		
OMA, each Lane	P <sub>OMA</sub>	-1.3		4.5	dBm	1	
Difference in Launch Power between any Two Lanes (OMA)	P <sub>tx,diff</sub>			5	dB		
Launch Power in OMA minus Transmitter and Dispersion Penalty (TDP), each Lane		-2.3			dBm		
TDP, each Lane	TDP			2.2	dB		
Extinction Ratio	ER	4			dB		
RIN <sub>20OMA</sub>	RIN			-130	dB/Hz		
Optical Return Loss Tolerance	TOL			20	dB		
Transmitter Reflectance	R <sub>T</sub>			-12	dB		
Average Launch Power OFF Transmitter, each Lane	P <sub>off</sub>			-30	dBm		
Eye Mask{X1, X2, X3, Y1, Y2, Y3}		{0.25, 0.4, 0.45, 0.25, 0.28, 0.4}					2

Receiver					
Damage Threshold, each Lane	TH <sub>d</sub>	5.5		dBm	3
Average Receive Power, each Lane		-10.6	4.5	dBm	
Receive Power (OMA), each Lane			4.5	dBm	
Receiver Sensitivity (OMA), each Lane	SEN		-8.6	dBm	
Stressed Receiver Sensitivity (OMA), each Lane			-6.8	dBm	4
Receiver Reflectance	R <sub>R</sub>		-26	dB	
Difference in Receive Power between any Two Lanes (OMA)	Prx,diff		5.5	dB	
LOS Assert	LOSA	-30		dBm	
LOS Deassert	LOSD		-13	dBm	
LOS Hysteresis	LOSH	0.5		dB	

Receiver Electrical 3 dB upper Cutoff Frequency, each Lane

F <sub>c</sub>	31	GHz
----------------	----	-----

Conditions of Stress Reliever Sensitivity Test Note(4)		
Vertical Eye Closure Penalty, each Lane	1.8	dB
Stressed Eye J2 Jitter, each Lane	0.3	UI
Stressed Eye J9 Jitter, each Lane	0.47	UI

1. Even if the TDP < 1 dB, the OMA min must exceed the minimum value specified here.
2. Hit ratio 5x10-5.
3. The receiver shall be able to tolerate, without damage, continuous exposure to a modulated optical input signal having this power level on one lane. The receiver does not have to operate correctly at this input power.
4. Measured with conformance test signal at receiver input for BER = 1x10-12.
5. Vertical eye closure penalty, stressed eye J2 jitter, and stressed eye J9 jitter are test conditions for measuring stressed receiver sensitivity. They are not characteristics of the receiver.

## Digital Diagnostics Functions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Temperature monitor absolute error	DMI_Temp	-3		+3	degC	Over operating temperature range
Supply voltage monitor absolute error	DMI_VCC	-0.1		0.1	V	Over full operating range
Channel RX power monitor absolute error	DMI_RX_Ch	-2		2	dB	1
Channel Bias current monitor	DMI_Ibias_Ch	-10%		10%	mA	
Channel TX power monitor absolute error	DMI_TX_Ch	-2		2	dB	1

Note(1): Due to measurement accuracy of different single mode fibers, there could be an additional +/-1 dB fluctuation, or a +/- 3 dB total accuracy

## Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Power Consumption				4.0	W	
Supply Current	I <sub>cc</sub>			1.21	A	
Transmitter (each lane)						
Overload Differential Voltage pk-pk	TP1a	900			mV	
Common Mode Voltage (V <sub>cm</sub> )	TP1	-350		2850	mV	1
Differential Termination Resistance Mismatch	TP1			10	%	At 1MHz
Differential Return Loss (SDD11)	TP1			See CEI-28G-VSR Equation 13-19	dB	
Common Mode to Differential conversion and Differential to Common Mode conversion (SDC11, SCD11)	TP1			See CEI-28G-VSR Equation 13-20	dB	
Stressed Input Test	TP1a		See CEI-28G-VSR Section 13.3.11.2.1			
Receiver(each lane)						
Differential Voltage, pk-pk	TP4			900	mV	
Common Mode Voltage (V <sub>cm</sub> )	TP4	-350		2850	mV	1
Common Mode Noise, RMS	TP4			17.5	mV	
Differential Termination Resistance Mismatch	TP4			10	%	At 1MHz
Differential Return Loss (SDD22)	TP4			See CEI-28G-VSR Equation 13-19	dB	
Common Mode to Differential conversion and Differential to Common Mode conversion (SDC22, SCD22)	TP4			See CEI-28G-VSR Equation 13-21	dB	
Common Mode Return Loss (SCC22)	TP4			-2	dB	2
Transition Time, 20 to 80%	TP4	9.5			ps	
Vertical Eye Closure (VEC)	TP4			5.5	dB	
Eye Width at 10 <sup>-15</sup> probability (EW15)	TP4	0.57			UI	
Eye Height at 10 <sup>-15</sup> probability (EH15)	TP4	228			mV	

Note(1): V<sub>cm</sub> is generated by the host. Specification includes effects of ground offset voltage.

Note(2): From 250MHz to 30GHz.