

# SV-QSFP-40G-PLR4

40G Base aggregating 4 x 1310nm SM wavelengths (MPO-12), distance up to 10km with DDM



## Features

- 4 Parallel lanes design
- Up to 11.2Gb/s data rate per channel
- Aggregate Bandwidth of up to 44.0G
- QSFP+ MSA compliant
- Up to 10km transmission on single mode fiber (SMF)
- Maximum power consumption 3.5W
- Single +3.3V power supply
- Operating case temperature: 0-70°C
- RoHS-6 compliant

## Applications

- 40G Ethernet
- Infiniband QDR, DDR and SDR
- Datacenter and Enterprise networking

Part number	Description
<b>SV-QSFP-40G-PLR4</b>	Starview QSFP+ 40Gbps module 40GBase aggregating 4 x 1310nm duplex SM (MPO-12) with Digital Diagnostic Monitoring (DDM), distance up to 10km, supporting 40GE, Infiniband QDR, DDR and SDR

## Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Unit
Storage Temperature	T <sub>s</sub>	-40	85	°C
Operating Case Temperature	T <sub>OP</sub>	0	70	°C
Power Supply Voltage	V <sub>CC</sub>	-0.5	3.6	V
Relative Humidity (non-condensation)	RH	0	85	%
Damage Threshold, each Lane	TH <sub>d</sub>	3.3		dBm

## Recommended Operating Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Operating Case Temperature	TOP	0		70	°C	
Power Supply Voltage	VCC	3.135	3.3	3.465	V	
Data Rate, each Lane			10.3125	11.2	Gb/s	
Control Input Voltage High		2		V <sub>CC</sub>	V	
Control Input Voltage Low		0		0.8	V	
Link Distance G652	D	0.002		10	km	

## Optical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
<b>Transmitter</b>						
Center Wavelength	λ <sub>C</sub>	1260	1310	1355	nm	
Side Mode Suppression Ratio	SMSR	30			dB	
Total Average Launch Power	PT			7.5	dBm	
Average Launch Power, each Lane	PAVG	-5.5		1.5	dBm	1
Optical Modulation Amplitude (OMA), each Lane	POMA	-4.5		2.5	dBm	2
Difference in Launch Power between any Two Lanes (OMA)	P <sub>tx,diff</sub>			6.5	dB	
Launch Power in OMA minus Transmitter and Dispersion Penalty (TDP), each Lane		-5.5			dBm	
TDP, each Lane	TDP			3.2	dB	
Extinction Ratio	ER	3.5			dB	
Relative Intensity Noise	RIN			-128	dB/Hz	
Optical Return Loss Tolerance	TOL			12	dB	
Transmitter Reflectance	RT			-12	dB	
Average Launch Power OFF Transmitter, each Lane	P <sub>off</sub>			-30	dBm	
Transmitter Eye Mask Definition {X1, X2, X3, Y1, Y2, Y3}		{0.25, 0.4, 0.45, 0.25, 0.28, 0.4}				
<b>Receiver</b>						
Center Wavelength	λ <sub>C</sub>	1260	1310	1355	nm	
Damage Threshold, each Lane	TH <sub>d</sub>	3.3			dBm	3

Average Power at Receiver Input, each Lane		-12.6	1.5	dBm	
Receiver Reflectance	RR		-12	dB	
Receive Power (OMA), each Lane			2.5	dBm	
Receiver Sensitivity in OMA, each Lane	SEN		-12.6	dBm	Infor-mative
Difference in Receive Power between any Two Lanes (OMA)	Prx,diff		7.5	dB	
LOS Assert	LOSA	-30		dBm	
LOS Deassert	LOSD		-15	dBm	
LOS Hysteresis	LOSH	0.5		dB	
Receiver Electrical 3 dB upper Cutoff Frequency, each Lane	Fc		12.3	GHz	

Note(1): The maximum transmitter average optical power of 1.5 dBm is well within the guardband of receiver overload specifications of commercially available 10GBASE-LR SFP+ transceivers offered by Starview and other vendors.

Note(2): Even if the TDP < 1 dB, the OMA min must exceed the minimum value specified here.

Note(3): The receiver shall be able to tolerate, without damage, continuous exposure to a modulated optical input signal having this power level on one lane. The receiver does not have to operate correctly at this input power.

## Digital Diagnostics Functions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Temperature monitor absolute error	DMI_Temp	-3		3	°C	Over operating temp
Supply voltage monitor absolute error	DMI_VCC	-0.1		0.1	V	Full operating range
Channel RX power monitor absolute error	DMI_RX_Ch	-2		2	dB	1
Channel Bias current monitor	DMI_Ibias_Ch	-10%		10%	mA	
Channel TX power monitor absolute error	DMI_TX_Ch	-2		2	dB	1

Note(1): Due to measurement accuracy of different single mode fibers, there could be an additional +/-1 dB fluctuation, or a +/- 3 dB total accuracy

## Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Power Consumption				3.5	W	
Supply Current	Icc			1,1	A	
Transceiver Power-on Initialization Time				2000	ms	1
Transmitter(each lane)						

Single-ended Input Voltage Tolerance (Note 2)		-0.3	4.0	V	Referred to TP1 signal common
AC Common Mode Input Voltage Tolerance (RMS)		15		mV	
Differential Input Voltage Swing Threshold		50		mVpp	LOSA Threshold
Differential Input Voltage Swing	Vin,pp	190	700	mVpp	
Differential Input Impedance	Zin	90	100	110	Ohm
Differential Input Return Loss		See IEEE 802.3ba 86A.4.11		dB	10MHz-11.1GHz
J2 Jitter Tolerance	Jt2	0.17		UI	
J9 Jitter Tolerance	Jt9	0.29		UI	
Data Dependent Pulse Width Shrinkage (DDPWS ) Tolerance		0.07		UI	
Eye Mask Coordinates {X1, X2 Y1, Y2}		0.11, 0.31 95, 350		UI mV	Hit Ratio = 5x10 <sup>-5</sup>
Receiver(each lane)					
Single-ended Output Voltage		-0.3	4.0	V	Referred to signal common
AC Common Mode Output Voltage (RMS)			7.5	mV	
Differential Output Voltage Swing	Vout,pp	300	850	mVpp	
Differential Output Impedance	Zout	90	100	110	Ohm
Termination Mismatch at 1MHz			5	%	
Differential Output Return Loss		See IEEE 802.3ba 86A.4.2.1		dB	10MHz-11.1GHz
Common Mode Output Return Loss		See IEEE 802.3ba 86A.4.2.2		dB	10MHz-11.1GHz
Output Transition Time		28		ps	20% to 80%
J2 Jitter Output	Jo2		0.42	UI	
J9 Jitter Output	Jo9		0.65	UI	
Eye Mask Coordinates {X1, X2 Y1, Y2}		0.29, 0.5 150, 425		UI mV	Hit Ratio = 5x10 <sup>-5</sup>

Note(1): Power-on Initialization Time is the time from when the power supply voltages reach and remain above the minimum recommended operating supply voltages to the time when the module is fully functional.

Note(2): The single ended input voltage tolerance is the allowable range of the instantaneous input signals