

SV-SFPP-6GLRD2H

Multi-rate 1.25Gbps to 6.25Gbps supporting CPRI and OBSAI Fiber Optic 1310nm SM, with DDM ,up to 20km



Features

- 10Gb/s serial optical interface compliant
- to 802.3ae 10GBASE-LR
- Electrical interface compliant to SFF-8431
- specifications for enhanced 8.5 and 10 Gigabit
- small form factor pluggable module "SFP+"
- 1310nm DFB transmitter, PIN photo-detector
- 2-wire interface for management
- specifications compliant with SFF 8472 digital
- diagnostic monitoring interface for optical transceivers
- Advanced firmware allow customer system
- encryption information to be stored in transceiver
- Cost effective SFP+ solution, enables higher
- port densities and greater bandwidth
- RoHS compliant

Applications

- High-speed storage area networks
- Computer cluster cross-connect
- Custom high-speed data pipes

Ordering Information

Part number	Description	TX Power (dBm)	RX Sens. (dBm)	Fiber Budget (dB)	Distance (km)	DDM
SV-SFPP-6GLRD2H	Starview SFP module Multi-rate 1.25Gbps to 6.25Gbps supporting CPRI and OBSAI Fiber Optic 1310nm SM (LC) with Digital Diagnostic Monitoring (DDM), Industrial temperature range, distance up to 20km	-8.2 to 0.5	-14.4 to 0.5	6.2	20	NO

Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit
Power Supply Voltage	VCC	0	3.6	V	
Storage Temperature	T _c	-40	85	°C	
Operating Case Temperature	T _c	-40	85	°C	
Relative Humidity	RH	5	95	%	
RX Input Average Power	Pmax	-	1.5	dBm	

Recommended Operating Environment

Parameter	Symbol	Min.	Typ.	Max.	Unit
Power Supply Voltage	VCC	3.135	3.3	3.465	V
Power Supply Current	I _{cc}			300	mA
Operating Case Temperature	T _C	-40		85	°C

Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Data Rate		-	10.3125	-	Gbps	
Power Consumption		-	800	1000	mW	
Transmitter						
Single Ended Output Voltage Tolerance		-0.3	-	4	V	
C common mode voltage tolerance		15	-	-	mV	
Tx Input Diff Voltage	V _I	180		700	mV	
Tx Fault	V _{oL}	-0.3		0.4	V	At 0.7mA
Data Dependent Input Jitter	DDJ			0.1	UI	
Data Input Total Jitter	T _J			0.28	UI	
Receiver						
Single Ended Output Voltage Tolerance		-0.3	-	4	V	
Rx Output Diff Voltage	V _O	300		850	mV	
Rx Output Rise and Fall Time	T _{r/Tf}	30			ps	20% to 80%
Total Jitter	T _J			0.7	UI	
Deterministic Jitter	D _J			0.42	UI	

Optical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Transmitter						
Center Wavelength	λ_t	1260		1355	nm	
Side Mode Suppression Ratio	SMSR	30			dB	
Average Optical Power	Pavg	-8.2	-	0.5	dBm	1
Laser Off Power	Poff	-	-	-30	dBm	
Extinction Ratio	ER	3.5	-	-	dB	
Transmitter Dispersion Penalty	TDP	-	-	3.2	dB	
Relative Intensity Noise	Rin	-	-	-128	dB/Hz	12dB reflection
Optical Return Loss Tolerance		-	-	12	dB	
Receiver						
Center Wavelength	λ_r	1260		1360	nm	
Receiver Sensitivity in average power	Psens	-	-	-14.4	dBm	1
Receiver Sensitivity in OMA	Psens	-	-	-12.6	dBm	2
Stressed Sensitivity (OMA)		-	-	-10.3	dBm	2
Vertical eye closure penalty		2.2			dB	3
Stressed eye jitter		0.3			UIp-p	2
Receive electrical 3dB upper cutoff frequency				12	GHz	
LOS Assert	LOSA	-30	-	-	dBm	
LOS Deassert	LOSD	-	-	-15	dBm	
LOS Hysteresis	LOSH	0.5	-	-	dB	
Overload	Pin	-	-	0.5	dBm	1
Receiver power damage				1.5	dBm	
Receiver Reflectance		-	-	-12	dB	

Note(1): Average optical power shall be measured using the methods specified in TIA/EIA-455-95.

Note(2): Receiver sensitivity is informative. Stressed receiver sensitivity shall be measured with conformance test signal for BER =1x 10-12 .

Note(3): Vertical eye closure penalty and stressed eye jitter are the test conditions for measuring stressed receiver sensitivity. They are not the required characteristic of the receiver.

Digital Diagnostic Functions

Parameter	Symbol	Min.	Max	Unit	Note
Temperature monitor absolute error	DMI_Temp	-3	3	degC	Over operating temp
Laser power monitor absolute error	DMI_TX	-3	3	dB	
RX power monitor absolute error	DMI_RX	-3	3	dB	-1dBm to -15dBm range

DATASHEET 4.1

Supply voltage monitor absolute error	DMI_VCC	-0.1	0.1	V	Full operating range
Bias current monitor	DMI_Ibias	-10%	10%	mA	