

SV-SFPP-6GLRDH

1.25Gbps to 6.25Gbps supporting CPRI and OBSAI Fiber Optic
1310nm SM (LC) with DDM, distance up to 2km



Features

- Up to 2km transmission distance
- FP transmitter and PIN photo-detector
- Duplex LC connector
- Metal enclosure, for lower EMI
- Electrical interface compliant to
- SFF-8431 specifications
- 2-wire interface for management specifications
- compliant with SFF-8472
- Single 3.3V power supply
- Case operating temperature range:
- -40°C to +85°C

Applications

- High-speed storage area networks
- OBSAI and CPRI
- LTE optical repeater application

Ordering Information

Part number	Description	TX Power (dBm)	RX Sens. (dBm)	Fiber Budget (dB)	Distance (km)	DDM
SV-SFPP-6GLRDH	Starview SFP module Multi-rate 1.25Gbps to 6.25Gbps supporting CPRI and OBSAI Fiber Optic 1310nm SM (LC) with Digital Diagnostic Monitoring (DDM), distance up to 2km, Industrial temperature range	-6.5 to 0.5	-14.4 to 0.5	7.9	2	Yes

Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit
Maximum Supply Voltage	Vcc	3.15		3.46	V
Storage Temperature	TS	-40		85	°C
Case Operating Temperature	Tcase	-40		85	°C

Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Supply Voltage	Vcc	3.15	3.3	3.46	V	
Supply Current	Icc			360	mA	
Transmitter						
Input differential impedance	Rin		100		Ω	1
Differential data input swing	Vin,pp	180		600	mV	
Transmit Disable Voltage	VD	Vcc-1.3		Vcc	V	
Transmit Enable Voltage	VEN	Vee		Vee+0.8	V	2
Transmit Disable Assert Time				10	us	
Receiver						
Differential data output swing	Vout,pp	300		850	mV	3
Data output rise time	tr	28			ps	4
Data output fall time	tf	28			ps	4
LOS Fault	VLOS fault	Vcc-1.3		VccHOST	V	5
LOS Normal	VLOS norm	Vee		Vee+0.8	V	5
Power Supply Rejection	PSR	100			mVpp	6

Note(1): Connected directly to TX data input pins. AC coupled thereafter.

Note(2): Or open circuit.

Note(3): Into 100 ohms differential termination.

Note(4): 20 – 80 % Measured with Module Compliance Test Board and OMA test pattern.

Note(5): Loss Of Signal is LVTTTL. Logic 0 indicates normal operation; logic 1 indicates no signal detected.

Note(6): Receiver sensitivity is compliant with power supply sinusoidal modulation of 20 Hz to 1.5 MHz up to specified value applied through the recommended power supply filtering network

Optical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Transmitter						
Average output power	POUT	-6.5		0.5	dBm	1
Optical Wavelength	λ	1260	1310	1355	nm	
RMS Spectral Width	σ			3.5	nm	
Optical Extinction Ratio	ER	3.5			dB	
Side mode Suppression ratio	SMSR	30			dB	
RIN	RIN			-128	dB/Hz	
Transmitter Jitter (peak to peak)		IEEE 802.3.ae requirements				
Receiver						
Receiver Sensitivity	Psen			-14.4	dBm	2
Input Saturation Power (Overload)	PSAT	0.5			dBm	
Input Optical Wavelength	λ_C	1270		1610	nm	
LOS De -Assert	LOSD			-18	dBm	
LOS Assert	LOSA	-30			dBm	
LOS Hysteresis		0.5	1		dB	

Note(1): Class 1 Laser Safety per FDA/CDRH and IEC-825-1 regulations.

Note(2): With worst-case extinction ratio. Measured with a PRBS 231-1 test pattern, BER<10⁻¹².