

SV-XFP-LR6xx

9.95Gbps to
11.1Gbps, 1270nmTX/1310nmRX
(1310nmTX/1270nmRX), SM, 60km



Features

- Hot-pluggable XFP footprint
- Supports 9.95Gb/s to 11.3Gb/s bit rates
- XFI Loopback Mode
- 1270nm DFB laser and APD receiver for SV-XFP-LR61
- 1330nm DFB laser and APD receiver for SV-XFP-LR62
- RoHS-6 Compliant (lead-free)
- Power dissipation < 3.5W
- Case operating temperature: 0 °C ~ 70 °C
- Up to 60km transmission on SMF
- 2-wire interface with integrated Digital Diagnostic monitoring
- EEPROM with Serial ID Functionality
- Compliant with XFP MSA with LC connector

Applications

- 10GBASE-BX 10.3125Gb/s Ethernet
- 10GBASE-BX 9.953Gb/s Ethernet
- SONET OC-192 & SDH STM I-64.1

Ordering Information

Part number	Description	TX Power (dBm)	RX Sens. (dBm)	Fiber Budget (dB)	Distance (km)	DDM
SV-XFP-LR61	Starview Single Fiber Bi-Directional XFP module with Digital Diagnostic Monitoring (DDM), Data rate from 9.95Gbps to 11.1Gbps supporting OC192/ STM64/ 10G LAN/ 10G FC, 1270nm TX/ 1330nm RX single fiber SM (LC), distance up to 60km	0 to 5	-20 to -6	20	60	YES
SV-XFP-LR62	Starview Single Fiber Bi-Directional XFP module with Digital Diagnostic Monitoring (DDM), Data rate from 9.95Gbps to 11.1Gbps supporting OC192/ STM64/ 10G LAN/ 10G FC, 1330nm TX/ 1270nm RX single fiber SM (LC), distance up to 60km	0 to 5	-20 to -6	20	60	YES

Absolute Maximum Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit
Storage Temperature	Ts	-40	-	85	°C
Storage Ambient Humidity	HA	5	-	95	%
Operating Relative Humidity	RH	-	-	85	%
Power Supply Voltage	VCC	-0.3	-	4	V
Signal Input Voltage	VCC	Vcc-0.3	-	Vcc+0.3	V

Recommended Operating Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Case Operating Temperature	Tcase	0	-	70	°C	Without air flow
Power Supply Voltage	VCC	3.14	3.3	3.47	V	
Power Supply Current	ICC	-	-	600	mA	
Data Rate	BR	9.95	10.3125	11.3	Gbps	
Transmission Distance	TD	2	-	60	km	
Coupled fiber		Single mode fiber				

Optical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Transmitter						
Average Launched Power	PO	0	-	5	dBm	
Average Launched Power(Laser Off)	POUT-OFF	-	-	-45	dBm	Note (1)
Centre Wavelength Range	λC	1260	1270	1280	nm	SV-XFP-LR61
		1320	1330	1340	nm	SV-XFP-LR62
Side mode suppression ratio	SMSR	30	-	-	dB	
Spectrum Bandwidth(-20dB)	σ	-	-	1	nm	
Extinction Ratio	ER	3.5	-	-	dB	Note (2)
Output Eye Mask	Compliant with IEEE 802.3ae requirements					Note (2)
Receiver						
Input Optical Wavelength	λIN	1320	1330	1340	nm	SV-XFP-LR61
		1260	1270	1280	nm	SV-XFP-LR62
Receiver Sensitivity in average	Psen	-	-	-20	dBm	Note (3)
Input Saturation Power (Overload)	PSAT	-6	-	-	dBm	Note (3)
LOS -Assert Power	PA	-38	-	-	dBm	
LOS -Deassert Power	PD	-	-	-21	dBm	
LOS -Hysteresis	PHys	0.5	-	4	dB	

Note (1): The optical power is launched into SMF

Note (2): Measured with RPBS 2^31-1 test pattern @10.3125Gbs

Note (3): Measured with RPBS 2^31-1 test pattern @10.3125Gbs BER=<10^-12

Electrical Interface Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Note
Total power supply current	I _{cc}	-	-	600	mA	
Transmitter						
Differential Data Input Voltage	VDT	120	-	820	mVp-p	
Differential line input Impedance	RIN	85	100	115	Ohm	
Transmitter Fault Output-High	VFaultH	2.4	-	V _{cc}	V	
Transmitter Fault Output-Low	VFaultL	-0.3	-	0.8	V	
Transmitter Disable Voltage- High	VDisH	2	-	V _{cc} +0.3	V	
Transmitter Disable Voltage- Low	VDisL	-0.3	-	0.8	V	
Receiver						
Differential Data Output Voltage	VDR	300	-	850	mVp-p	
Differential line Output Impedance	ROUT	80	100	120	Ohm	
Receiver LOS Pull up Resistor	RLOS	4.7	-	10	KOhm	
Data Output Rise/Fall time	tr/ff	20	-	-	ps	
LOS Output Voltage-High	VLOSH	2	-	V _{cc}	V	
LOS Output Voltage-Low	VLOSL	-0.3	-	0.4	V	